



Cleaning the Fan Blades

Follow this guide to clean the fan blades.

Written By: Vivian Fong



INTRODUCTION

This guide will disassemble the fan to clean the fan blades.



TOOLS:

- [Phillips #2 Screwdriver](#) (1)
 - [Soft Cloth](#) (1)
-

Step 1 — PCB (Printed Circuit Board)




- Use the Phillips #2 screwdriver to remove the four 6 mm screws by unscrewing counterclockwise.

Step 2



- Pull the front and back cover apart.
- ⚠ Be careful not to pull the front cover off completely. It holds the wires.

Step 3



- Remove the Phillips 6 mm screw that holds the circuit board to the outer shell of the fan.



⚠ Shock warning: Make sure the fan is unplugged before removing the circuit board.

Step 4




- Remove the top cover containing the circuit board and the wires by pulling it away from the outer shell of the fan.

Step 5



- Remove the screws from the four corners of the circuit board.
 - Remove the circuit board from the top cover.
- ⚠ Do not touch the other side of the circuit board to avoid damaging the circuit elements.

Step 6 — Fan Blades



- Follow steps 1-4 to remove the front, back, and top covers of the fan to reach the fan blades.
- Use a cloth to clean off dust clogged in between the fan blades.

To reassemble your device, follow these instructions in reverse order.