



# LG Stylo 3 Plus Rear Camera Replacement

Is the rear camera on your LG Stylo 3 Plus no...

Written By: Patricia Pires Dias



# INTRODUCTION

Is the rear camera on your LG Stylo 3 Plus no longer taking great photos? Removing the rear camera for cleaning or replacement may sound daunting, but it only takes about 5 minutes and some simple tools. Follow this guide to quickly replace your rear camera and continue taking great pictures!

---

## TOOLS:

[iFixit Opening Tool](#) (1)

[Phillips #000 Screwdriver](#) (1)

[Tweezers](#) (1)

---

## Step 1 — Back Cover



 Power off the phone before beginning disassembly.

- Place the phone face down.
- Insert a fingernail or a plastic opening tool into the gap on the side of the phone.
- Carefully slide your finger or the tool throughout the edge of the phone to ease the back case off.

## Step 2 — Battery



- Place the back cover off to the side.
- Insert the opening tool into the small gap below the battery.
- Carefully pop the battery out to prevent damage.

## Step 3 — Rear Camera



- Remove the twelve 4mm screws using the Phillips #000 screwdriver.
- Use the plastic opening tool to remove the inner case.
- Carefully remove the inner case.

## Step 4



- Use your fingernail or the plastic opening tool to flip the flex cable.
- Use the precision [tweezers](#) to carefully grasp and pull out the camera.

---

To reassemble your device, follow these instructions in reverse order.