


BlackBerry 7100g Housing Replacement

Written By: Kellan



INTRODUCTION

This guide shows how to replace the BlackBerry 7100g external housing case.



TOOLS:

- Spudger (1)
- T6 Torx Screwdriver (1)
- iFixit Opening Tools (1)

Step 1 — Battery



- Turn over your BalckBerry 7100g so that the back cover is facing up.
- Locate the battery cover release button near the bottom of the back panel.

Step 2







- Push down on the release button with one thumb.
- Slide the battery cover off with the other thumb.

Step 3



 Remove the battery from the battery housing by flipping up the top of the battery.

Step 4 — Housing







- Locate the silver strip near the top of your BlackBerry.
- Use a plastic opening tool to pry off the edge of the silver lining.
- Slide the tool along the length of the silver strip to completely remove it.

Step 5





- (i) Do not lose the screws. They are quite small and can easily be misplaced.
- Locate and unscrew the four (4) screws using a T6 screwdriver.

Step 6







- The keypad cover may fall out of the housing when prying the housing apart.
- Tightly pinch the top of the front and back halves of the housing.
- Carefully pry the two halves of the housing apart.

Step 7



 You can now easily remove the "guts" of the phone from the housing.

To reassemble your device, follow these instructions in reverse order.