



# Xbox 360 Wireless Controller Rear Case Replacement

Stop holding your Xbox 360 wireless controller...

Written By: Brett Hartt



# INTRODUCTION

Stop holding your Xbox 360 wireless controller together with duct tape. Use this guide to replace your old broken rear case.

---

## TOOLS:

[Spudger](#) (1)

[T8 Torx Security Bit Screwdriver](#) (1)

[Tweezers](#) (1)

---

### Step 1 — Battery



- Depress the battery release button on the top of the controller.
  - Remove the battery holder from the controller.
- ⓘ The standard option for Xbox 360 Wireless Controllers Battery Packs is AA batteries. A rechargeable battery is also available, but both battery options are removed from the controller in the same way.

## Step 2 — Rear Case



- Use a pair of [tweezers](#) to peel the barcode sticker from the battery compartment.

## Step 3



- Remove the seven 9.3 mm T8 Security Torx screws securing the rear case to the front case.



## Step 4



- Insert a [Spudger](#) between the front and rear cases along the left edge of the controller.
- Rotate the spudger toward the front of the controller, prying the two cases apart.

## Step 5



- Insert a spudger between the front and rear cases, near the headphone jack.
- Rotate the spudger toward the front of the controller to pry the two cases apart.

## Step 6



- Grasp the controller by the battery compartment and the headphone jack.
- Lift the battery compartment away from the headphone jack, separating the rear case from the front case and logic board.
- ☑ The battery contact springs are held in place by slots in the battery housing in the rear case. Be sure to realign them properly during reassembly.

---

To reassemble your device, follow these instructions in reverse order.