



# Patching a Bicycle Tire Inner Tube

This guide will show how to patch a tire on the specialized expedition.

Written By: Travis Tonder



## INTRODUCTION

You will be taking the wheel off of your bike, removing the tire from the wheel, and patching the hole.

Notes:

- Make sure that the wheel is fully deflated throughout the process, except for finding the hole.
- When applying the rubber cement to the hole, the thinner the layer the better, for faster drying.



### TOOLS:

- [Bike Pump](#) (1)
- [Rubber Cement](#) (1)
- [Sand Paper](#) (1)
- [Tire Lever](#) (1)



### PARTS:

- [Tire Patch](#) (1)

## Step 1 — Rear Wheel



- Flip the quick release lever on the wheel.

## Step 2



- Squeeze the brake arms together and lift the brake cable from the caliper arms.

### Step 3



- Hold the wheel to the ground, and pull the bike frame up and away to remove the wheel from the bike.

### Step 4 — Inner Tube



- Press the valve core while applying pressure to the tire to deflate the tire.

## Step 5



- Insert the flat part of a tire lever under the tire coping. Apply pressure to the other end of the lever to lift the tire up and out of the wheel.
- Slide the lever around the circumference of the wheel to completely remove the tire.
- ⓘ Alternatively, if you have multiple tire levers, see if you can clip the first lever to a spoke to keep it in place. Then insert the second lever a few inches away. Clip it to a spoke. Insert the third lever a few more inches along. Take out the second lever and insert it a few inches past the third. Work along the rim until the tire pops off.

## Step 6



- Remove the tube by pushing the valve through the hole in the rim and pulling the tube out from under the tire.

## Step 7 — Patching a Bicycle Tire Inner Tube



- Press the valve core while applying pressure to the tire to deflate the tire.

## Step 8



- Insert the flat part of a tire lever under the tire coping. Apply pressure to the other end of the lever to lift the tire up and out of the wheel.
- Slide the lever around the circumference of the wheel to completely remove the tire.

## Step 9



- Remove the tube by pushing the valve through the hole in the rim and pulling out completely.

## Step 10



- Locate the leak by first over inflating the tire.
- Place the tire under water and look for bubbles to find the leak.

## Step 11



- Mark the hole with a marker, and completely deflate the tire.

## Step 12



- Select a patch kit that you will use to patch the hole. Try to pick a patch that is appropriate for the size of the hole.

## Step 13



- Clean the area near the hole with soap and water, then dry it thoroughly.
- Rough up the area around the hole with an abrasive surface such as sand paper until the area around the leak loses its shine.

## Step 14



- Apply rubber cement to an area around the hole that is bigger than the patch to ensure that the patch bonds completely.

## Step 15



- Apply the patch to the area.

## Step 16



- Apply pressure to the patch until the rubber cement is dry.

To reassemble your wheel, follow these instructions in reverse order starting at step three.