



# Samsung Galaxy Tab 8.9 Speaker(s) Replacement

This guide will walk you through the process of...

Written By: Eric Bird



# INTRODUCTION

This guide will walk you through the process of replacing distorted or broken speakers on a Samsung Galaxy Tab 8.9.

---

## TOOLS:

[iFixit Opening Tool](#) (2)


[Lead-Free Solder](#) (1)

[Portable Soldering Iron](#) (1)

[Desoldering Braid](#) (1)

---

## Step 1 — Insert Opening tool




- Insert a plastic opening tool between the back cover and screen of the Samsung Galaxy Tab 8.9 (as indicated in the photograph).

## Step 2 — Insert second tool



- Insert a second plastic opening tool 6 cm (~2.4 inches) away from the first tool.

## Step 3




- Slide the second plastic opening tool along the edge of the device to separate the back cover.

## Step 4



- Using your hands, remove the back cover.


## Step 5 — Charging Port



- Using [tweezers](#), peel away the green tape located on top of the two flexible ribbon cables.




## Step 6




- Insert a spudger under the orange tab.
- Pry open the tab to disconnect the black flexible ribbon cable from the motherboard.

## Step 7




- Slide out the yellow flexible ribbon cable to disconnect it from the motherboard.

## Step 8




- Using a Phillips #00 screwdriver, unscrew the 4 screws (3mm) that are holding the charger port and speaker support.

## Step 9




- Insert opening tool to pry support from the housing.

## Step 10



- Desolder the two connections to separate the speakers from the charger port.

## Step 11



- Separate charging port from speaker assembly.

---

To reassemble your device, follow these instructions in reverse order.